



KRIL®

OUR CLASSIC EXTERIOR PAINT



Our classic, 100% acrylic, high-build exterior paint. It has strong adhesion, good durability and exceptional color retention. Kril is formulated to be mold and mildew resistant and is available in four sheens and an extensive color selection. It is ideal for any commercial or residential building, including those with wood, concrete, stucco, or manufactured siding. Kril's ease of application makes it the perfect paint for anyone from the average homeowner to the experienced professional.

- 100% Acrylic
- Self-Priming
- Excellent Color Retention
- Water Clean Up

FLAT

A flat finish will minimize visibility of surface imperfections due to light refraction. It is best used for rough surfaces, or surfaces that are regularly repainted or touched up.

VELVET

Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed. This finish has a minimal sheen that is mostly seen at an angle. It reduces dirt pick-up and provides some washability. Ideal for full body exterior work where some sheen is desired. Best used when the surface is free of major imperfections.

SATIN

This finish will minimize dirt pick-up and is washable. Ideal for full body exterior work where some sheen is desired. Best used when the surface is free of major imperfections.

SEMI GLOSS

This high-sheen product is very washable and perfect for areas that are more susceptible to dirt, grease, and moisture. Use in applications like exterior smooth siding, exterior smooth wood trim, and primed metal surfaces.



KRIL®

OUR CLASSIC EXTERIOR PAINT



SPECIFICATIONS FOR KRIL

	FLAT	VELVET	SATIN	SEMIGLOSS
VOLUME SOLIDS	35.4%	35.0%	32.7%	36.1%
VISCOSITY	100-105 KU	100-105 KU	100-105 KU	100-105 KU
WEIGHT PER GALLON	11.4 (LB)	10.9 (LB)	10.42 (LB)	10.3 (LB)
GLOSS	0-5% @60° 0-5% @85°	5-10% @60° 7-15% @85°	10-20% @60° 30-45% @85°	45-55% @60°
V.O.C. (MINUS WATER)	46.0 G/L	48.0 G/L	46.0 G/L	45.0 G/L

COVERAGE: Approximately 250-400 square feet per gallon. @ 1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface. Properly prepared surfaces provide the best coverage.

DRY TIME: One hour to touch and four hours to recoat @ 70°F and 50% relative humidity.

ABOUT MILLER PAINT

Established in 1890, Miller Paint is an employee owned company with a proud Northwest tradition of creating products made for our unique Northwest climate. From our humble beginnings as a family-run company, to a company with over 300 employees and over 50 locations, Miller Paint has always been there for the professional and homeowner alike.

For a location near you, go to www.millerpaint.com

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the specification will be revised. Miller and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR. REV 9/16