



ACRINAMEL®

MULTIPURPOSE ACRYLIC ENAMEL



A top quality, multipurpose acrylic enamel ideal for exterior/interior projects. Acrinamel provides an exceptionally durable finish for exterior and interior surfaces that require a moisture resistant, washable coating. Ideal for exterior metal and fine wood, as well as interior wood, masonry, and metal surfaces. Its durable, moisture-resistant film provides the performance of an enamel finish with the benefits of a water clean up and low odor.

- High quality 100% acrylic enamel
- Excellent color and sheen retention
- Excellent resistance to moisture
- Soap and water clean up

EGGSHELL

Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed. Also applicable for commercial or residential projects that require minimal washability such as conference rooms, living rooms, or bedrooms.

SATIN

This finish will minimize dirt pick-up and is washable. With the hard finish of an enamel, a satin finish can also be used on interior walls where a strong, durable moisture resistant surface is

needed. Best used when the surface is free of major imperfections. Use in applications such as interior primed smooth or rough walls, exterior or interior finish grade wood trim, or primed metal surfaces.

SEMIGLOSS

This high-sheen product is very washable and perfect for areas that are more susceptible to dirt, grease, and moisture. Use in applications such as institutional walls, trim, and wet areas, exterior or interior doors, exterior or interior finish grade wood trim, or primed metal surfaces.



ACRINAMEL®

MULTIPURPOSE ACRYLIC ENAMEL



Specifications For Acrinamel

	EGGSHELL	SATIN	SEMIGLOSS
VOLUME SOLIDS	35.9%	32.1%	33.2%
VISCOSITY	100-105 KU	100-105 KU	103-108 KU
WEIGHT PER GALLON	11.01 (LB)	10.67 (LB)	10.39 (LB)
GLOSS	5-10% @60°	10-20% @60°	45-55% @60°
V.O.C. (MINUS WATER)	<50 G/L	48.9 G/L	47.5 G/L

COVERAGE: Approximately 350-400 square feet per gallon @1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface.

DRY TIME: One hour to touch and four hours to recoat @70°F and 50% relative humidity.



ABOUT MILLER PAINT

Established in 1890, Miller Paint is an employee owned company with a proud Northwest tradition of creating products made for our unique Northwest climate. From our humble beginnings as a family-run company, to a company with over 300 employees and over 50 locations, Miller Paint has always been there for the professional and homeowner alike.

For a location near you, go to www.millerpaint.com

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the specification will be revised. Miller and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR. REV 9/16