



PERFORMANCE PLUS®

THE PROFESSIONAL'S CHOICE



Designed for the professional and the homeowner alike, the Performance Plus line of products provides a consistent, reliable quality finish. The modified PVA resin has been proven to provide good coverage and value. Performance Plus applies easily to indoor surfaces such as smooth or textured walls and ceilings. Performance Plus interior finish is an outstanding product for use on new wallboard, smooth or textured, in living rooms, bedrooms, hallways and ceilings. The low odor and low VOC formulation make it a great choice for commercial, industrial, and institutional spaces.

- Low odor
- Easy to apply
- Splatter resistant
- Easy clean-up with water
- MPI certified

FLAT

A flat finish will minimize visibility of surface imperfections. It is ideal for theatre and performing arts and residential or commercial projects where no sheen is desired and minimal traffic will be expected. Ideal for ceilings or in formal living and dining rooms. Perfect for use on walls with uneven surfaces.

EGGSHELL

Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed. Also applicable for commercial or residential projects that require minimal washability such as conference rooms, new homes, living rooms or bedrooms.

SATIN

This finish will minimize dirt pick-up and is washable. Ideal for projects where a deep, rich look and some sheen and washability are desired, such as offices, hotel rooms, conference rooms, apartments, or homes.

SEMIGLOSS

This high-sheen product is very washable and perfect for areas that are more susceptible to dirt, grease and moisture. Ideal for projects in high traffic areas such as waiting rooms, restaurants and other public areas, as well as kitchens, bathrooms and laundry rooms.



PERFORMANCE PLUS®

THE PROFESSIONAL'S CHOICE



Specifications For Performance Plus

	FLAT	EGGSHELL	SATIN	SEMIGLOSS
VOLUME SOLIDS	29.1%	31.4%	33.0%	32.0%
VISCOSITY	95-100 KU	95-100 KU	95-100 KU	95-100 KU
WEIGHT PER GALLON	10.9 (LB)	10.9 (LB)	10.5 (LB)	10.4 (LB)
GLOSS	<5% @60°	5-10% @60°	10-20% @60°	45-55% @60°
V.O.C. (MINUS WATER)	31.0 G/L	45.0 G/L	45.0 G/L	28.0 G/L

COVERAGE: Approximately 250-300 square feet per gallon @1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface.

DRY TIME: One hour to touch and four hours to recoat @70°F and 50% relative humidity.



ABOUT MILLER PAINT

Established in 1890, Miller Paint is an employee owned company with a proud Northwest tradition of creating products made for our unique Northwest climate. From our humble beginnings as a family-run company, to a company with over 300 employees and over 50 locations, Miller Paint has always been there for the professional and homeowner alike.

For a location near you, go to www.millerpaint.com

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the specification will be revised. Miller and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR. REV 9/16