



MetroPaint™ Recycled Latex Paint Interior/Exterior Low-Sheen

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.
Date of issue: 01/11/2016 Revision date: 02/06/2018 Version: 2.2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : MetroPaint™ Recycled Latex Paint Interior/Exterior Low-Sheen

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Paint

1.3. Details of the supplier of the safety data sheet

MetroPaint
4825 N Basin Ave
Portland, OR 97217 - USA
T 503-289-0047
OregonMetro.gov/MetroPaint

1.4. Emergency telephone number

Jim Quinn, Program Manager : Cell phone: (503) 957-2150

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Not classified.

2.2. Label elements

GHS-US labeling

No labelling applicable.

2.3. Other hazards

No additional information available.

2.4. Unknown acute toxicity (GHS US)

Not applicable.

SECTION 3: Composition/information on ingredients

3.1. Substance

This product consists primarily of post-consumer recyclable latex paints. Feedstock may vary.

3.2. Mixture

Name	Product identifier	%
Titanium dioxide	(CAS No) 13463-67-7	5 - 25
Limestone	(CAS No) 1317-65-3	1 - 10
Quartz	(CAS No) 14808-60-7	1 - 5
Zinc oxide	(CAS No) 1314-13-2	1 - 5
Ethylene glycol	(CAS No) 107-21-1	< 5

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

MetroPaint™ Recycled Latex Paint Interior/Exterior Low-Sheen

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Treat for surrounding material.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon and vinyl acetate monomer.
Explosion hazard	: Containers may explode when heated.

5.3. Advice for firefighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--

6.2. Methods and material for containment and cleaning up

For containment	: Dike and contain spill. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for cleaning up	: Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.
Hygiene measures	: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep out of the reach of children. Keep container tightly closed. Do not freeze. Do not store near strong oxidizing agents. Store away from direct sunlight or other heat sources.
--------------------	--

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium dioxide (13463-67-7)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
Limestone (1317-65-3)		
ACGIH	Not applicable.	
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)

MetroPaint™ Recycled Latex Paint Interior/Exterior Low-Sheen

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	(30)/(%SiO ₂ + 2) mg/m ³ TWA (total dust) (250)/(%SiO ₂ + 5) mppcf TWA (respirable fraction) (10)/(%SiO ₂ + 2) mg/m ³ TWA (respirable fraction)
Zinc oxide (1314-13-2)		
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (respirable fraction)
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ (respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Ethylene glycol (107-21-1)		
ACGIH	ACGIH Ceiling (mg/m ³)	100 mg/m ³ (aerosol only)
OSHA	Not applicable.	

8.2. Exposure controls

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	: Impermeable gloves as needed to avoid repeated or prolonged exposure.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Pigmented emulsion coating
Color	: Varies
Odor	: Slight ammonia
Odor threshold	: No data available
pH	: Varies (typical 8.0 to 9.0)
Melting point	: No data available
Freezing point	: 32 °F (0 °C)
Boiling point	: 212 °F
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: Faster than ether, 50-70% volatile (volume)
Flammability (solid, gas)	: Not flammable
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: Heavier than air
Solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available

MetroPaint™ Recycled Latex Paint Interior/Exterior Low-Sheen

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Viscosity	: Varies (typical 95 to 105 KU at 77 °F)
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Temperatures below 32°F and above 90°F.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon and vinyl acetate monomer.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

MetroPaint™ Recycled Latex Paint Interior/Exterior Low-Sheen	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	No data available
Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg
Zinc oxide (1314-13-2)	
LD50 oral rat	> 5000 mg/kg
Ethylene glycol (107-21-1)	
LD50 oral rat	4700 mg/kg
LD50 dermal rat	10600 mg/kg

Skin corrosion/irritation	: Based on available data, the classification criteria are not met.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitization	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met. Normal application procedures pose no hazard, because the titanium dioxide and silica are wet and encapsulated. However, grinding or sanding dried films of this product may yield respirable titanium dioxide and silica dusts.

Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans (airborne particles of respirable size)
Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans (airborne particles of respirable size)
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens

Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: Based on available data, the classification criteria are not met.

MetroPaint™ Recycled Latex Paint Interior/Exterior Low-Sheen

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

MetroPaint™ Recycled Latex Paint Interior/Exterior Low-Sheen

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

MetroPaint™ Recycled Latex Paint Interior/Exterior Low-Sheen

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available.

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated for transport

Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Ethylene glycol (107-21-1)

Subject to reporting requirements of United States SARA Section 313

EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule
--------------------------	---

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

15.3. US State regulations

MetroPaint™ Recycled Latex Paint Interior/Exterior Low-Sheen

State or local regulations	This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
----------------------------	--

SECTION 16: Other information

Date of issue : 01/11/2016

Revision date : 02/06/2018

Version : 2.2

Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.