



ACRO PURE®

ENVIRONMENTALLY RESPONSIBLE



Acro Pure line of paints are low odor, ultra-low VOC*, and certified Indoor Advantage Gold for indoor air quality.



Acro Pure paints are 100% acrylic, providing excellent coverage and durability for interior residential and commercial spaces. An environmentally-responsible paint, Acro Pure is the perfect choice for homes, schools, and healthcare environments.

- Ultra-Low VOC
- Thick and creamy
- Stain resistant
- Excellent splatter resistance
- Washable

FLAT

A flat finish will minimize visibility of surface imperfections due to lack of light refraction. It is less washable and therefore ideal for theater/performing arts and residential or commercial projects where no sheen is desired and minimal traffic will be expected. Ideal for ceilings and walls with uneven surfaces.

EGGSHELL

Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed. Also applicable for commercial or residential projects that require minimal washability such as conference rooms, living rooms, or bedrooms.

SATIN

This finish will minimize dirt pick-up and is washable. Ideal for projects where a deep, rich look and some sheen is desired, such as offices, hotel rooms, bedrooms, or hallways.

SEMIGLOSS

This high-sheen product is very washable and perfect for areas that are more susceptible to dirt, grease and moisture. Ideal for projects in high traffic areas such as waiting rooms, restaurants, and other public areas.



ACRO PURE®

ENVIROMENTALLY RESPONSIBLE



Specifications For Acro Pure Wall Finish

	FLAT	EGGSHELL	SATIN	SEMIGLOSS
VOLUME SOLIDS	39.25%	34.7%	36.2%	34.2%
VISCOSITY	98-103 KU	98-103 KU	98-103 KU	98-103 KU
WEIGHT PER GALLON	11.73 (LB)	11.12 (LB)	10.7 (LB)	10.3 (LB)
GLOSS	<5% @60°	5-10% @60°	10-20% @60°	45-55% @60°
V.O.C. (MINUS WATER)	<6 G/L	<6 G/L	<6 G/L	<6 G/L

COVERAGE: Approximately 350-450 square feet per gallon @ 1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface.

DRY TIME: One hour to touch and four hours to recoat @ 70°F and 50% relative humidity.

ABOUT MILLER PAINT

Established in 1890, Miller Paint is an employee owned company with a proud Northwest tradition of creating products made for our unique Northwest climate. From our humble beginnings as a family-run company, to a company with over 300 employees and over 50 locations, Miller Paint has always been there for the professional and homeowner alike.

For a location near you, go to www.millerpaint.com

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the specification will be revised. Miller and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR. REV 9/16