



# STRATUS XT™

## EXTERIOR VELVET 5202XX

### Exterior Siding & Trim Paint

Built to protect your home or building from our Pacific Northwest weather, Stratus XT is a 100% acrylic exterior coating with good color retention and durability. Formulated for our climate, Stratus XT is ideal for use on any commercial or residential building year round. Easy to apply by brush, roller, or sprayer, Stratus XT is suitable for most exterior substrates including wood, concrete, stucco, and manufactured siding. Designed to withstand climate shifts from extreme heat to high humidity, Stratus XT is a versatile exterior coating available in Flat, Velvet, and Satin sheens.

#### PRODUCT INFORMATION

<b>Resin:</b>	Acrylic	<b>Weight Per Gallon:</b>	10.9 lbs.
<b>Color Range:</b>	White and Custom Tints	<b>Solids by Weight:</b>	52% ± 2%
<b>Finish:</b>	4 – 20 @ 85° Gloss Level 2	<b>Solids by Volume:</b>	35% ± 2%
<b>Drying Time:</b>	To Touch: 1 hour	<b>Recommended Film Thickness:</b>	Wet: 4-5 mils. Dry: 1.5 – 2 mils.
<b>(70° F. &amp; 50% R.H.)</b>	To Recoat: 2 hours	<b>Practical Coverage:</b>	250 – 400 Sq. Ft. Per Gallon
<b>Clean Up:</b>	Water	<b>VOC:</b>	<50 g/L*
<b>Sizes:</b>	Gallons, Fives	*Maximum VOC content for non-tinted paint base is less than 50 g/L (40 CFT 59.406). VOC content may increase after tinting product.	
<b>Tint Bases:</b>	White    Deep    Neutral		
	520205   520225   520240		

#### REGULATORY COMPLIANCE

Architectural and Industrial Maintenance Coating (AIM - EPA) GreenSeal GS-11 Standard  
South Coast Air Quality Management District (SCAQMD)  
California Air Resources Board (CARB)

#### SURFACE PREPARATION

**General:**  
All surfaces must be firm, dry and cleaned free of loose paint, dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. De-gloss shiny surfaces by lightly sanding†. Repair cracks and fill voids.

†See warning for existing lead-based paint under Precautions.

#### New Surfaces:

Follow general surface preparation guidelines. New concrete or stucco must cure for 30 days prior to coating. Moisture content should be less than 12 % as measured with a moisture meter and the pH should be between 7 and 11. Remove all laitance and efflorescence before priming with the appropriate primer.

#### Previously Painted Surfaces:

Follow general surface preparation guidelines. Remove loose or failing paint and spot prime bare areas or entire surface with the appropriate primer. Hard, glossy surfaces may require sanding and/or a bonding primer.

Surface and air temperatures should be between 35°F and 95°F during application. Humidity should be below 80%. Surface temperature should be at least 5°F above dew point. Do not paint if temperatures are expected to drop below 35°F.

#### RECOMMENDED PRIMERS

- Concrete, Stucco, and Masonry:**
  - pH Surfacers Alkali Resistant Primer 620011
- Concrete Block:**
  - Kril Int/Ext Block Filler 481011
- Wood:**
  - All Purpose Int/Ext Stain Blocking Primer 470011
  - Alkyd Wood Bond Exterior Primer 670011
- Ferrous Metal, Galvanized Metal, or Aluminum:**
  - Acrimetel DTM Low Sheen Primer/Finish 310210
  - All Purpose Int/Ext Stain Blocking Primer 470011
- Gypsum Wallboard:**
  - All Purpose Int/Ext Stain Blocking Primer 470011
  - pH Surfacers Alkali Resistant Primer 620011

*OTHER PRIMERS MAY BE APPROPRIATE. CONTACT MILLER PAINT FOR MORE INFORMATION.*

Spraying and Backrolling recommended on new flat work. To avoid lap marks, maintain a wet edge. Keep product from freezing.

#### APPLICATION

- Brush:** Nylon/Polyester Brush
- Roller:** 3/8" – 3/4" Nap Synthetic Cover
- Airless Spray:** .017" - .021" Tip Size

#### THINNING

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon. Stir product thoroughly.

#### PRECAUTIONS

**WARNING!** If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information, consult the Material Safety Data Sheet for this product.

**USE ONLY WITH ADEQUATE VENTILATION.**

**KEEP OUT OF REACH OF CHILDREN.**

#### WARRANTY

**LIMITED 15 YEAR WARRANTY:** If this Miller Paint StratusXT Paint, when applied in accordance with label instructions and technical data sheet, blisters or peels within 15 years from the date of purchase, then Miller Paint Co., Inc. will either provide an equivalent paint product in an amount sufficient for repair free of charge, or refund the original purchase price, but only upon presentation of original proof of purchase. This warranty, which excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint, inadequate surface preparation or application of the product, extends only to the owner of the single-family home to which the paint was applied during such owner's occupancy, may not be transferred or assigned, and is your sole and exclusive remedy. THIS WARRANTY DOES NOT INCLUDE LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT, AND EXCLUDES ANY INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion of incidental or consequential damages, so the limitation may not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state.

#### DISPOSAL

Never pour leftover coating down any sink or drain – use up material on the job or seal can and store safely for future use. Do not incinerate closed containers. For specific disposal or recycle guidelines, contact your local waste management agency or district. Please re-use or recycle.