



ACRI-LITE®

Our Most Popular Exterior Paint



Setting the quality standard for exterior painting in the Pacific Northwest for more than 50 years, Acri-Lite is our most popular and widely used exterior paint. Made from 100% acrylic resin and formulated for our unique climate, Acri-Lite has superior adhesion, durability, and hide. With early moisture resistance, low temperature application, and protection against peeling and cracking, Acri-Lite is a flexible exterior coating designed to perform at the highest level despite changes in weather. Available in Flat, Velvet, Satin, and Semigloss sheens, Acri-Lite has excellent color retention and fade resistance for a long-lasting finish.

- All-weather exterior formulation for the Pacific Northwest
- 100% acrylic resin
- Excellent color retention
- High build, flexible coating
- Outstanding adhesion
- Superior hide and coverage
- Dirt and stain resistant
- Mold and mildew resistant
- Low temp application down to 35°F
- Limited 25 year warranty

FLAT

A flat finish will minimize visibility of surface imperfections due to lack of light refraction. It is best used for rough surfaces or surfaces that are regularly repainted or touched up.

VELVET

Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed, and mostly seen at an angle. It reduces dirt pick-up and provides some washability. Ideal for full body exterior work where some sheen is desired. Best used when the surface is free of major imperfections.

SATIN

This finish will minimize dirt pick-up and is washable. Ideal for full body exterior work where some sheen is desired. Best used when the surface is free of major imperfections. Use in applications like exterior body, sidings (wood or metal), exterior rough or smooth trim.

SEMIGLOSS

This high-sheen product is very washable and perfect for areas that are more susceptible to dirt, grease and moisture. Use in applications like exterior smooth siding, exterior smooth wood trim, and primed metal surfaces.



ACRI-LITE®

Our Most Popular Exterior Paint

SPECIFICATIONS FOR ACRI-LITE

	FLAT	VELVET	SATIN	SEMIGLOSS
Volume Solids	41.9%	42.5%	39.0%	39.0%
VISCOSITY	100-105 KU	100-105 KU	100-105 KU	100-105 KU
Weight Per Gallon	11.5 (LB)	11.2 (LB)	10.6 (LB)	10.2 (LB)
Gloss	3-5%@60°	4-6%@60°	10-20%@60°	45-55%@60°
V.O.C. (minus water)	49.0 g/L	45.5 g/L	47.0 g/L	50.0 g/L

COVERAGE: Approximately 350-475 square feet per gallon. @ 1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface. Properly prepared surfaces provide the best coverage.

DRY TIME: One hour to touch and four hours to recoat @ 70°F and 50% relative humidity.

SPECIFICATIONS FOR SUPER ACRI-LITE

	VELVET	SATIN	SEMIGLOSS
Volume Solids	45.0%	42.7%	42.0%
VISCOSITY	100-105 KU	100-105 KU	100-105 KU
Weight Per Gallon	11.9 (LB)	11.0 (LB)	10.6 (LB)
Gloss	4-6%@60°	10-20%@60°	45-55%@60°
V.O.C. (minus water)	48.0 g/L	49.0 g/L	50.0 g/L

COVERAGE: Approximately 350-475 square feet per gallon. @ 1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface. Properly prepared surfaces provide the best coverage.

DRY TIME: One hour to touch and four hours to recoat @ 70°F and 50% relative humidity.

ABOUT MILLER PAINT

Manufactured in Portland, Oregon since 1890, Miller Paint is an employee-owned company with over 50 stores throughout Oregon, Washington and Idaho. Miller Paint products are specifically formulated for the Pacific Northwest climate and are known for outstanding quality and durability. Praised for exceptional customer service and color expertise, Miller Paint is the region's go-to paint for homeowners and professionals alike.

For a location near you, go to www.millerpaint.com

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the specification will be revised. Miller and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR. REV 9/16