



# ACRO HP®

The Next Step in Environmentally Responsible Paint



Acro HP is a low odor, high performance 100% acrylic interior coating. Formulated to provide outstanding protection and performance for high-traffic areas. It is an excellent choice for new or previously painted wall and ceiling surfaces including wallboard, plaster, concrete, primed metal and wood surfaces. A great choice for professional offices, medical and care facilities, or other occupied spaces where low odor and low VOC levels are preferred.

- 100% acrylic cross-linking resin
- Ultra-low VOC\*
- Low odor
- Highly scrubbable interior wall finishes
- Excellent stain resistance
- Antimicrobial enhanced
- Water clean up

## EGGSHELL

Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed. Also applicable for commercial or residential projects such as conference rooms, living rooms, or bedrooms.

## SATIN

This finish will minimize dirt pick-up and is washable. Ideal for projects where a deep, rich look and some sheen is desired, such as offices, hotel rooms, bedrooms, or hallways. Use in applications such as interior primed smooth or rough walls, exterior or interior finish grade wood trim, or primed metal surfaces.

## SEMIGLOSS

This high-sheen product is very washable and perfect for areas that are more susceptible to dirt, grease and moisture. Ideal for projects in high traffic areas such as waiting rooms, restaurants, and other public areas.



# ACRO HP®

The Next Step in Environmentally Responsible Paint



## Specifications for Acro Pure Wall Finish

	EGGSHELL	SATIN	SEMIGLOSS
Volume Solids	35.96%	35.59%	35.2%
Viscosity	98-103 KU	98-103 KU	98-103 KU
Weight Per Gallon	11.05 (LB)	10.69 (LB)	10.18 (LB)
Gloss	5-10%@60°	10-20%@60°	45-55%@60°
V.O.C. (minus water)	<6 g/L	<6 g/L	<6 g/L

**COVERAGE:** Approximately 350-450 square feet per gallon @ 1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface

**DRY TIME:** One hour to touch and four hours to recoat @70°F and 50% relative humidity.



## ABOUT MILLER PAINT

Established in 1890, Miller Paint is an employee owned company with a proud Northwest tradition of creating products made for our unique Northwest climate. From our humble beginnings as a family-run company, to a company with over 300 employees and over 50 locations, Miller Paint has always been there for the professional and homeowner alike.

For a location near you, go to [www.millerpaint.com](http://www.millerpaint.com)

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the specification will be revised. Miller and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR. REV 9/16