



# Super Color



Miller Paint's Super Color line combines superior performance with the convenience of high-hiding power. Designed to provide exceptional hide and easy application in brighter and lighter colors, Super Colors are available in red, yellow, and white bases. 100% acrylic and suitable for interior and exterior use, Super Color finishes include Velvet, Satin, and Semigloss.

- **Superior Hide**
- **Easy Application**
- **Interior & Exterior**
- **100% Acrylic**
- **Available in Velvet, Satin, and Semigloss Sheens**

## FLAT

A flat finish will minimize visibility of surface imperfections due to lack of light refraction. It is best used for rough surfaces or surfaces that are regularly repainted or touched up.

## VELVET

Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed, and mostly seen at an angle. It reduces dirt pick-up and provides some washability. Ideal for full body exterior work where some sheen is desired. Best used when the surface is free of major imperfections.

## SATIN

This finish will minimize dirt pick-up and is washable. Ideal for full body exterior work where some sheen is desired. Best used when the surface is free of major imperfections. Use in applications like exterior body, sidings (wood or metal), exterior rough or smooth trim.

## SEMIGLOSS

This high-sheen product is very washable and perfect for areas that are more susceptible to dirt, grease and moisture. Use in applications like exterior smooth siding, exterior smooth wood trim, and primed metal surfaces.



## SPECIFICATIONS FOR SUPER COLOR FINISH

	VOLUME SOLIDS	VISCOSITY	WEIGHT PER GAL	GLOSS	VOC (MINUS WATER)
INT SUPER WHITE EGGSHELL	40.5	95-100 KU	10.97	5-10% @ 60°	<50
INT SUPER WHITE SATIN	39.3	95-100 KU	10.35	10-20% @ 60°	<50
INT SUPER WHITE SEMIGLOSS	36.5	95-100 KU	10.95	45-55% @ 60°	<50
EXT SUPER WHITE VELVET	46.5	100-105 KU	11.93	4-20% @ 60°	<50
EXT SUPER WHITE SATIN	44.4	100-105 KU	11.12	10-20% @ 60°	<50
EXT SUPER WHITE SEMIGLOSS	44.4	100-105 KU	10.56	45-55% @ 60°	<50
SUPER RED VELVET	27.4	105-110 KU	9.59	4-20% @ 60°	<100
SUPER RED SATIN	26.5	105-110 KU	9.14	10-20% @ 60°	<100
SUPER RED SEMIGLOSS	26	105-110 KU	8.79	45-55% @ 60°	<100
SUPER YELLOW VELVET	26.4	105-110 KU	9.96	4-20% @ 60°	<100
SUPER YELLOW SATIN	26.5	105-110 KU	9.96	10-20% @ 60°	<100
SUPER YELLOW SEMIGLOSS	27	105-110 KU	9.96	45-55% @ 60°	<100



**COVERAGE:** Approximately 300-400 square feet per gallon @ 1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface.

**DRY TIME:** One hour to touch and four hours to recoat @ 70°F and 50% relative humidity.

## ABOUT MILLER PAINT

Manufactured in Portland, Oregon since 1890, Miller Paint is an employee-owned company with over 50 stores throughout Oregon, Washington and Idaho. Miller Paint products are specifically formulated for the Pacific Northwest climate and are known for outstanding quality and durability. Praised for exceptional customer service and color expertise, Miller Paint is the region's go-to paint for homeowners and professionals alike.

For a location near you, go to [www.millerpaint.com](http://www.millerpaint.com)

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the specification will be revised. Miller and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR. REV 9/16