



Evolution® Exterior

OUR FINEST PAINT



With over 130 years of quality paint-making, Evolution® Exterior is our most technologically-advanced coating. Formulated with a 100% pure acrylic co-polymer resin system developed for prolonged adhesion, guards against mildew growth. Previously painted surfaces can be refreshed in a single coat, while new projects require two-saving time from prep through completion. This high-solids exterior coating provides superior coverage and long-lasting durability. Born out of our roots in the Pacific Northwest, each gallon of Evolution Exterior paint boasts early moisture resistance and enhanced UV protection. Evolution Exterior's flexible, smooth finish retains color brilliance and resists fade, even on darker colors. Make your home a part of our legacy with Evolution, Our Finest Paint.

- All-weather exterior formulation for the Pacific Northwest
- Advanced 100% acrylic system
- Enhanced UV protection and fade resistance
- Early moisture and surfactant resistance
- Superior coverage and long-lasting durability
- Excellent flexibility minimizes cracking and peeling
- Reduced dirt pick up
- Inhibits mold and mildew growth
- Low temp application down to 35°F
- Limited lifetime warranty

VELVET

Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed. This finish has a minimal sheen that is mostly seen at an angle. It reduces dirt pick-up and provides some washability. Ideal for full body exterior work where some sheen is desired. Best used when the surface is free of major imperfections.

SATIN

This finish will minimize dirt pick-up and is washable. Ideal for full-body exterior work where some sheen is desired. Best used when the surface is free of major imperfections.



SPECIFICATIONS FOR EVOLUTION EXTERIOR PAINT

	VELVET	SATIN
VOLUME SOLIDS	42.6%	41.4%
VISCOSITY	100-105 KU	100-105 KU
WEIGHT PER GALLON	11.26 (LB)	11 (LB)
GLOSS	2-6% @60° 5-20% @85°	10-20% @60° 30-45% @85°
VOC* (MINUS WATER)	49 G/L	49 G/L

*MAXIMUM VOC CONTENT FOR THIS PRODUCT AS PER 40 CFR 59.406



COVERAGE: Approximately 250 - 500 square feet per gallon. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface. Properly prepared surfaces provide the best coverage.

DRY TIME: 30 minutes to touch and 2 hours to recoat @ 70°F and 50% relative humidity.

LIMITED LIFETIME WARRANTY: If this Miller Paint Evolution Exterior Paint, when applied in accordance with label instructions and technical data sheet, blisters or peels for as long as you own the single-family home to which this paint was applied, then Miller Paint Co., Inc. will either provide an equivalent paint product in an amount sufficient for repair free of charge, or refund the original purchase price, but only upon presentation of original proof of purchase. This warranty, which excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint, inadequate surface preparation or application of the product, extends only to the owner of the single-family home to which the paint was applied during such owner’s occupancy, may not be transferred or assigned, and is your sole and exclusive remedy. THIS WARRANTY DOES NOT INCLUDE LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT, AND EXCLUDES ANY INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion of incidental or consequential damages, so the limitation may not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state.

ABOUT MILLER PAINT

Manufactured in Portland, Oregon since 1890, Miller Paint is an employee-owned company with over 50 stores throughout Oregon, Washington and Idaho. Miller Paint products are specifically formulated for the Pacific Northwest climate and are known for outstanding quality and durability. Praised for exceptional customer service and color expertise, Miller Paint is the region’s go-to paint for homeowners and professionals alike.

For a location near you, go to www.millerpaint.com

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the specification will be revised. Miller and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR. REV 8/26